

Pocket filter

Nanowave ePM1 50%

APPLICATIONS

- Fine filtration for air handling units and prefiltration for (H) EPA filters

ADVANTAGES

- Very low initial resistance
- High dust-holding capacity, long service life
- Low energy consumption
- Self-supporting medium
- Eurovent certified through the manufacturer

SPECIFICATIONS

- Media: Nanowave synthetic
- Frame: Galvanized steel, also available in wood and plastic
- Recommended final resistance: 250 Pa
- Maximum continuous temperature: 70° Celsius
- Maximum relative humidity: 100%



ARTICLE NUMBER	WIDTH MM.	HEIGHT MM.	LENGTH MM.	NUMBER OF POCKETS	ISO 16890	EN 779	FLOW RATE M3/H	INITIAL RESISTANCE	ENERGY USAGE
01060052	287	287	360	4	ePM1 50%	F7	850	162	>2050
01060051	287	592	360	4	ePM1 50%	F7	1700	162	>2050
01060054	490	592	360	6	ePM1 50%	F7	2800	162	>2050
01060050	592	287	360	8	ePM1 50%	F7	1700	162	>2050
01060053	592	490	360	8	ePM1 50%	F7	2800	162	>2050
01060049	592	592	360	8	ePM1 50%	F7	3400	162	>2050
01060046	287	287	500	4	ePM1 50%	F7	850	100	1396
01060045	287	592	500	4	ePM1 50%	F7	1700	100	1396
01060048	490	592	500	6	ePM1 50%	F7	2800	100	1396
01060044	592	287	500	8	ePM1 50%	F7	1700	100	1396
01060047	592	490	500	8	ePM1 50%	F7	2800	100	1396
01060043	592	592	500	8	ePM1 50%	F7	3400	100	1396
01060040	287	287	600	4	ePM1 50%	F7	850	92	1295
01060039	287	592	600	4	ePM1 50%	F7	1700	92	1295
01060042	490	592	600	6	ePM1 50%	F7	2800	92	1295
01060038	592	287	600	8	ePM1 50%	F7	1700	92	1295
01060041	592	490	600	8	ePM1 50%	F7	2800	92	1295
01060037	592	592	600	8	ePM1 50%	F7	3400	92	1295

Alternative sizes on request

TOPS Luchtfilters
Rondven 38
6026 PX Maarheeze (NL)

Tel +31 (0)40 - 204 54 06
E-mail info@topsluchtfilters.nl
Web www.topsluchtfilters.nl

KvK 60526009
BTW NL142262638B01
IBAN NL21 RABO 0122 7145 71

