

# Pocket filter

## Synthetic Coarse 65%

### APPLICATIONS

- Coarse (pre)filtration for air handling units and air inlet grilles
- Exhaust air filtration

### ADVANTAGES

- High dust-holding capacity
- Low pressure drop
- Conical self-supporting bags
- Applicable within the food industry
- Eurovent certified through the manufacturer

### SPECIFICATIONS

- Media: Synthetic with progressive build-up
- Frame: Galvanized steel, also available in wood and plastic
- Recommended final resistance: 250 Pa
- Maximum continuous temperature: 80° Celsius
- Maximum relative humidity: 100%



ARTICLE NUMBER	WIDTH MM.	HEIGHT MM.	LENGTH MM.	NUMBER OF POCKETS	ISO 16890	EN 779	FLOW RATE M3/H	INITIAL RESISTANCE	ENERGY USAGE
01010052	287	287	360	3	Coarse 65%	G4	850	37	
01010051	287	592	360	3	Coarse 65%	G4	1700	37	
01010238	287	892	360	3	Coarse 65%	G4	2550	37	
01010054	490	592	360	5	Coarse 65%	G4	2800	37	
01010283	490	892	360	5	Coarse 65%	G4	4200	37	
01010050	592	287	360	6	Coarse 65%	G4	1700	37	
01010053	592	490	360	6	Coarse 65%	G4	2800	37	
01010049	592	592	360	6	Coarse 65%	G4	3400	37	
01010313	592	892	360	6	Coarse 65%	G4	5100	37	

Alternative sizes on request

ARTICLE NUMBER	WIDTH MM.	HEIGHT MM.	LENGTH MM.	NUMBER OF POCKETS	ISO 16890	EN 779	FLOW RATE M3/H	INITIAL RESISTANCE	ENERGY USAGE
01010046	287	287	500	3	Coarse 65%	G4	850		
01010045	287	592	500	3	Coarse 65%	G4	1700		
01010239	287	892	500	3	Coarse 65%	G4	2550		
01010048	490	592	500	5	Coarse 65%	G4	2800		
01010284	490	892	500	5	Coarse 65%	G4	4200		
01010044	592	287	500	6	Coarse 65%	G4	1700		
01010047	592	490	500	6	Coarse 65%	G4	2800		
01010043	592	592	500	6	Coarse 65%	G4	3400		
01010314	592	892	500	6	Coarse 65%	G4	5100		
01010040	287	287	600	3	Coarse 65%	G4	850	30	
01010039	287	592	600	3	Coarse 65%	G4	1700	30	
01010240	287	892	600	3	Coarse 65%	G4	2550	30	
01010042	490	592	600	5	Coarse 65%	G4	2800	30	
01010285	490	892	600	5	Coarse 65%	G4	4200	30	
01010038	592	287	600	6	Coarse 65%	G4	1700	30	
01010041	592	490	600	6	Coarse 65%	G4	2800	30	
01010037	592	592	600	6	Coarse 65%	G4	3400	30	
01010315	592	892	600	6	Coarse 65%	G4	5100	30	

Alternative sizes on request