

# Absolute filter Pak H13

## APPLICATIONS


- Cleanroom supply and exhaust air
- Inline and Terminal Enclosures
- Pharmaceutical manufacturing, laboratories, semiconductor/ microelectronics manufacturing and healthcare

## ADVANTAGES

- Compact and lightweight
- Easy to install and replace
- Low pressure drop
- Two-component polyurethane molded or flat neoprene gasket for a perfect seal

## SPECIFICATIONS

- Media: Water resistant micro fiberglass
- Frame: Extruded anodized aluminum, waterproof MDF or galvanized steel
- Spacers: Thermoplastic hot melt
- Maximum continuous temperature: 70° Celsius
- Maximum relative humidity: 100%



ARTICLE NUMBER	WIDTH MM.	LENGTH MM.	THICKNESS MM.	THICKNESS PLEAT PACK MM.	EN 1822	ISO 29463	FLOW RATE M3/H	INITIAL RESISTANCE	EFFICIENCY
	305	305	78		H13	ISO 35 H	250	250	99,95000%
	305	610	78		H13	ISO 35 H	500	250	99,95000%
	610	610	78		H13	ISO 35 H	100	250	99,95000%
	305	305	150		H13	ISO 35 H	500	250	99,95000%
	305	610	150		H13	ISO 35 H	1000	250	99,95000%
	610	610	150		H13	ISO 35 H	2000	250	99,95000%
	305	305	292		H13	ISO 35 H	750	250	99,95000%
	305	610	292		H13	ISO 35 H	1500	250	99,95000%
	610	610	292		H13	ISO 35 H	3000	250	99,95000%

Alternative sizes on request