

Pocket filter

Nanowave Plus ePM1 90%

APPLICATIONS

- Can be used in recirculation systems

ADVANTAGES

- Neutralises 99% of virus particles
- Reduces virus spread in ducts for 12 months
- Eurovent certified through the manufacturer
- LIST certified against COVID-19
- High dust-holding capacity

SPECIFICATIONS

- Medium: Nanowave synthetic with virucide coating
- Frame: Galvanized steel
- Recommended final resistance: 300Pa
- Maximum continuous temperature: 80° Celsius
- Maximum relative humidity: 100%
- Energy label A+



ARTICLE NUMBER	WIDTH MM.	HEIGHT MM.	LENGTH MM.	NUMBER OF POCKETS	ISO 16890	EN 779	FLOW RATE M3/H	INITIAL RESISTANCE	ENERGY USAGE
01060107	287	287	400	5	ePM1 90%	F9	850	98	1198
01060105	287	592	400	5	ePM1 90%	F9	1700	98	1198
01060106	490	592	400	8	ePM1 90%	F9	2800	98	1198
01060116	592	287	400	11	ePM1 90%	F9	1700	98	1198
01060115	592	490	400	11	ePM1 90%	F9	2800	98	1198
01060114	592	592	400	11	ePM1 90%	F9	3400	98	1198