

Absolute filter Pak E11

APPLICATIONS


- Cleanroom supply and exhaust air
- Inline and Terminal Enclosures
- Pharmaceutical manufacturing, laboratories, semiconductor/ microelectronics manufacturing and healthcare

ADVANTAGES

- Compact and lightweight
- Easy to install and replace
- Low pressure drop
- Two-component polyurethane molded or flat neoprene gasket for a perfect seal

SPECIFICATIONS

- Media: Water resistant micro fiberglass
- Frame: Extruded anodized aluminum, waterproof MDF or galvanized steel
- Spacers: Thermoplastic hot melt
- Maximum continuous temperature: 70° Celsius
- Maximum relative humidity: 100%



ARTICLE NUMBER	WIDTH MM.	LENGTH MM.	THICKNESS MM.	THICKNESS PLEAT PACK MM.	EN 1822	ISO 29463	FLOW RATE M3/H	INITIAL RESISTANCE	EFFICIENCY
	305	305	78		E11	ISO 15 E			95,00000%
	305	610	78		E11	ISO 15 E			95,00000%
	610	610	78		E11	ISO 15 E			95,00000%
	305	305	150		E11	ISO 15 E			95,00000%
	305	610	150		E11	ISO 15 E			95,00000%
	610	610	150		E11	ISO 15 E			95,00000%
	305	305	292		E11	ISO 15 E			95,00000%
	305	610	292		E11	ISO 15 E			95,00000%
	610	610	292		E11	ISO 15 E			95,00000%

Alternative sizes on request