

# Pocket filter

## Activated carbon Coarse 65%

### APPLICATIONS

- Coarse (pre)filtration for air handling units
- Exhaust air filtration
- Capture of odors and gases
- For airports, offices etc

### ADVANTAGES

- The aerodynamic shape reduces turbulence in the airflow
- Tapered pockets reduce pressure drop
- Low energy consumption
- High dust-holding capacity

### SPECIFICATIONS

- Media: Fiber glass with activated carbon granulate
- Frame: Galvanized steel, also available in wood and plastic
- Recommended final resistance: 250 Pa
- Maximum continuous temperature: 70° Celsius
- Maximum relative humidity: 70%



ARTICLE NUMBER	WIDTH MM.	HEIGHT MM.	LENGTH MM.	NUMBER OF POCKETS	ISO 16890	EN 779	FLOW RATE M3/H	INITIAL RESISTANCE	ENERGY USAGE
	287	287	500	3	Coarse 65%	G4	850	35	
	287	592	500	3	Coarse 65%	G4	1700	35	
	592	287	500	6	Coarse 65%	G4	1700	35	
	592	490	500	6	Coarse 65%	G4	2800	35	
	592	592	500	6	Coarse 65%	G4	3400	35	
	287	287	600	3	Coarse 65%	G4	850	30	
	287	592	600	3	Coarse 65%	G4	1700	30	
	592	287	600	6	Coarse 65%	G4	1700	30	
	592	490	600	6	Coarse 65%	G4	2800	30	
01040013	592	592	600	6	Coarse 65%	G4	3400	30	

Alternative sizes on request