

Pocket filter

Nanowave ePM1 60%

APPLICATIONS

- Fine filtration for air handling units and prefiltration for (H) EPA filters

ADVANTAGES

- Very low initial resistance
- High dust-holding capacity, long service life
- Low energy consumption
- Self-supporting medium
- Eurovent certified through the manufacturer

SPECIFICATIONS

- Media: Nanowave synthetic
- Frame: Galvanized steel, also available in wood and plastic
- Recommended final resistance: 250 Pa
- Maximum continuous temperature: 70° Celsius
- Maximum relative humidity: 100%



ARTICLE NUMBER	WIDTH MM.	HEIGHT MM.	LENGTH MM.	NUMBER OF POCKETS	ISO 16890	EN 779	FLOW RATE M3/H	INITIAL RESISTANCE	ENERGY USAGE
01060034	287	287	360	4	ePM1 60%	F7	850	126	1870
01060033	287	592	360	4	ePM1 60%	F7	1700	126	1870
01060036	490	592	360	6	ePM1 60%	F7	2800	126	1870
01060032	592	287	360	8	ePM1 60%	F7	1700	126	1870
01060035	592	490	360	8	ePM1 60%	F7	2800	126	1870
01060031	592	592	360	8	ePM1 60%	F7	3400	126	1870
01060028	287	287	500	4	ePM1 60%	F7	850	85	1254
01060027	287	592	500	4	ePM1 60%	F7	1700	85	1254
01060030	490	592	500	6	ePM1 60%	F7	2800	85	1254
01060026	592	287	500	8	ePM1 60%	F7	1700	85	1254
01060029	592	490	500	8	ePM1 60%	F7	2800	85	1254
01060025	592	592	500	8	ePM1 60%	F7	3400	85	1254
01060022	287	287	600	4	ePM1 60%	F7	850	74	950
01060021	287	592	600	4	ePM1 60%	F7	1700	74	950
01060024	490	592	600	6	ePM1 60%	F7	2800	74	950
01060020	592	287	600	8	ePM1 60%	F7	1700	74	950
01060023	592	490	600	8	ePM1 60%	F7	2800	74	950
01060019	592	592	600	8	ePM1 60%	F7	3400	74	950

Alternative sizes on request

Tops Luchtfilters B.V.
Platinastraat 34
6031 TW Nederweert

Tel +31 (0)40 - 204 54 06
E-mail info@topsluchtfilters.nl
Web www.topsluchtfilters.nl

KvK 69099456
BTW NL857733692B01
IBAN NL 21 RABO 0122 7145 71