

Pocket filter

Nanowave ePM1 70%

APPLICATIONS

- Fine filtration for air handling units and prefiltration for (H) EPA filters

ADVANTAGES

- Very low initial resistance
- High dust-holding capacity, long service life
- Low energy consumption
- Self-supporting medium
- Eurovent certified through the manufacturer

SPECIFICATIONS

- Media: Nanowave synthetic
- Frame: Galvanized steel, also available in wood and plastic
- Recommended final resistance: 250 Pa
- Maximum continuous temperature: 70° Celsius
- Maximum relative humidity: 100%



ARTICLE NUMBER	WIDTH MM.	HEIGHT MM.	LENGTH MM.	NUMBER OF POCKETS	ISO 16890	EN 779	FLOW RATE M3/H	INITIAL RESISTANCE	ENERGY USAGE
01060016	287	287	360	4	ePM1 70%	F8	850	150	>2150
01060015	287	592	360	4	ePM1 70%	F8	1700	150	>2150
01060018	490	592	360	6	ePM1 70%	F8	2800	150	>2150
01060014	592	287	360	8	ePM1 70%	F8	1700	150	>2150
01060017	592	490	360	8	ePM1 70%	F8	2800	150	>2150
01060013	592	592	360	8	ePM1 70%	F8	3400	150	>2150
01060010	287	287	500	4	ePM1 70%	F8	850		
01060009	287	592	500	4	ePM1 70%	F8	1700		
01060012	490	592	500	6	ePM1 70%	F8	2800		
01060008	592	287	500	8	ePM1 70%	F8	1700		
01060011	592	490	500	8	ePM1 70%	F8	2800		
01060007	592	592	500	8	ePM1 70%	F8	3400		
01060004	287	287	600	4	ePM1 70%	F8	850	81	1067
01060003	287	592	600	4	ePM1 70%	F8	1700	81	1067
01060006	490	592	600	6	ePM1 70%	F8	2800	81	1067
01060002	592	287	600	8	ePM1 70%	F8	1700	81	1067
01060005	592	490	600	8	ePM1 70%	F8	2800	81	1067
01060001	592	592	600	8	ePM1 70%	F8	3400	81	1067

Alternative sizes on request

Tops Luchtfilters B.V.
Platinastraat 34
6031 TW Nederweert

Tel +31 (0)40 - 204 54 06
E-mail info@topsluchtfilters.nl
Web www.topsluchtfilters.nl

KvK 69099456
BTW NL857733692B01
IBAN NL 21 RABO 0122 7145 71