

Pocket filter

Nanowave ePM1 90%

APPLICATIONS

- Fine filtration for air handling units and prefiltration for (H) EPA filters

ADVANTAGES

- Very low initial resistance
- High dust-holding capacity, long service life
- Low energy consumption
- Self-supporting medium
- Eurovent certified through the manufacturer

SPECIFICATIONS

- Media: Nanowave synthetic
- Frame: Galvanized steel, also available in wood and plastic
- Recommended final resistance: 250 Pa
- Maximum continuous temperature: 70° Celsius
- Maximum relative humidity: 100%



ARTICLE NUMBER	WIDTH MM.	HEIGHT MM.	LENGTH MM.	NUMBER OF POCKETS	ISO 16890	EN 779	FLOW RATE M3/H	INITIAL RESISTANCE	ENERGY USAGE
01060070	287	287	360	4	ePM1 90%	F9	850	228	>2500
01060069	287	592	360	4	ePM1 90%	F9	1700	228	>2500
01060072	490	592	360	6	ePM1 90%	F9	2800	228	>2500
01060068	592	287	360	8	ePM1 90%	F9	1700	228	>2500
01060071	592	490	360	8	ePM1 90%	F9	2800	228	>2500
01060067	592	592	360	8	ePM1 90%	F9	3400	228	>2500
01060064	287	287	500	4	ePM1 90%	F9	850	155	2001
01060063	287	592	500	4	ePM1 90%	F9	1700	155	2001
01060066	490	592	500	6	ePM1 90%	F9	2800	155	2001
01060062	592	287	500	8	ePM1 90%	F9	1700	155	2001
01060065	592	490	500	8	ePM1 90%	F9	2800	155	2001
01060061	592	592	500	8	ePM1 90%	F9	3400	155	2001
01060058	287	287	600	4	ePM1 90%	F9	850	119	1397
01060057	287	592	600	4	ePM1 90%	F9	1700	119	1397
01060060	490	592	600	6	ePM1 90%	F9	2800	119	1397
01060056	592	287	600	8	ePM1 90%	F9	1700	119	1397
01060059	592	490	600	8	ePM1 90%	F9	2800	119	1397
01060055	592	592	600	8	ePM1 90%	F9	3400	119	1397

Alternative sizes on request

Tops Luchtfilters B.V.
Platinastraat 34
6031 TW Nederweert

Tel +31 (0)40 - 204 54 06
E-mail info@topsluchtfilters.nl
Web www.topsluchtfilters.nl

KvK 69099456
BTW NL857733692B01
IBAN NL 21 RABO 0122 7145 71