

# Pocket filter

## Rigid ePM1 65%

### APPLICATIONS

- Fine filtration for air handling units and prefiltration for (H) EPA filters
- Suitable for filtration in any environmental condition and climate

### ADVANTAGES

- 100% synthetic, corrosion free and moisture resistant
- Self-supporting, leak-proof welded bags: Remains rigid in turbulent airflows
- Maximum dust-holding capacity; unique design and medium
- Aerodynamic wedge-shaped, tubular spacers for minimum resistance and maximum power
- Pockets integrated in injection-molded, impact-resistant PU header for a burst strength of < 6000 Pa

### SPECIFICATIONS

- Media: Rigid synthetic
- Frame: Plastic
- Recommended final resistance: 250 Pa
- Maximum continuous temperature: 70° Celsius
- Maximum relative humidity: 100%



ARTICLE NUMBER	WIDTH MM.	HEIGHT MM.	LENGTH MM.	NUMBER OF POCKETS	ISO 16890	EN 779	FLOW RATE M3/H	INITIAL RESISTANCE	ENERGY USAGE
01090027	289	595	600	4	ePM1 65%	F7	1700	150	
01090026	493	595	600	5	ePM1 65%	F7	2800	150	
01090025	595	595	600	8	ePM1 65%	F7	3400	150	

Alternative sizes on request